

Magnetic stirrer

digital, 80-1,500 rpm, ceramic-coated plate 180x180 mm



80-1500
rpm



Stirrer bar included

MS-20D digital

Ideal for:

- mixing of chemical, laboratory and pharmaceutical materials

Features:

- digital display with backlight
- shade motor for 80-1,500 rpm
- ceramic-coated aluminium plate 180x180 mm
- heat-, chemical- and restricted acid-resistant
- powder-coated aluminium body
- 30 mm stirrer bar included
- CE certified and unique serial number for tracing

Safety mechanism:

- timer 99h 59min with timer-end signal
- error status
- locking mode
- operation LEDs

Controller:

- **Jog-Shuttle** controller with touch-button

Model	MS-20D
Body	powder-coated aluminium
Plate	ceramic-coated aluminium (heat-, chemical- and acid-resistant), 180x180 mm
Stirring capacity	max. 20 l
Speed & control resolution	80 ~ 1,500 rpm, 5 rpm
Timer & alarm	99hr 59min (with continuous run), error status and timer-end
Display	digital LCD with backlight function
Controller	digital feedback controller with Jog-Shuttle Switch (Turn+Push)
Stirring bar	30 mm bar included, usable up to 50 mm bar
Permissible temperature & RH %	ambient temperature +5 ~ 50°C, 85% RH
Dimension & weight	206x307xh99 mm, 3.1 kg
Packaging size	400x280xh200 mm, 5 kg
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz
Order number 230V	DH.WMS03022
Order number 120V	DH.WMS02022

Votre revendeur :



42 à 48 Bd de Polangis - BP 260 - 94502 Champigny-sur-Marne Cedex
Tél.: 01 48 83 21 76 - Fax.: 01 48 83 51 01 info@cloup.fr www.cloup.fr