

PLC12 SERIES CONNECTOR



The 1/4" flow polypropylene PLC12 offers many of the same configuration options as the PLC. The polypropylene material adds greater chemical resistance for more demanding applications. PLC12 couplings are also gamma sterilizable. PLC12 couplings are also gamma sterilizable and available with optional RFID (Radio Frequency Identification) capability (see page 96).

FEATURES

Polypropylene material

EPDM o-rings

CPC thumb latch

Integral terminations

BENEFITS

Chemically resistant and gamma sterilizable

Greater chemical resistance

One-hand connection and disconnection

Fewer leak points, shorter assemblies, faster installations

Specifications

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

32°F to 160°F (0°C to 71°C)

MATERIALS:

Main components and valves:

Polypropylene

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: EPDM

STERILIZATION:

Gamma: Up to 50 kGy irradiation

COLOR:

Almond

TUBING SIZES:


1/4" to 3/8" ID, 6.4mm to 9.5mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions. Use the graph at the right as a guide.


PLC12 Couplings are gamma sterilizable; see page 162 for more information on sterilization and disinfection

These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.


PLC12 Air Flow, 100 psig Inlet Pressure



PLC12 Water Flow



PLC12 Pressure Range



Liquid Flow Rate Information for Couplings

The chart below shows the flow rate for CPC couplings. Each coupling was tested with water at 70°F (21°C). To determine flow rates for specific coupling configurations use the formula at the right.

$$Q = C_v \sqrt{\frac{\Delta P}{S}}$$


Q = Flow rate in gallons per minute
C_v = Average coefficient across various flow rates (see chart)
ΔP = Pressure drop across coupling (psi)
S = Specific gravity of liquid

C_v VALUES FOR 1/4" FLOW PLC12 COUPLINGS

BODIES	INSERTS	PLC12 20004	PLCD12 20004	PLC12 20006	PLCD12 20006	PLC12 22004	PLCD12 22004	PLC12 22006	PLCD12 22006	PLC12 24004	PLCD12 24004	PLC12 24006	PLCD12 24006	PLC12 26004
	PLC1000412	.40	.36	1.05	.58	.83	.56	1.40	.82	1.40	.75	1.40	.77	.83
	PLCD1000412	.36	.31	.73	.48	.66	.41	.82	.50	.80	.45	.77	.45	.81
	PLC1000612	.40	.36	1.05	.60	.83	.56	1.40	.81	1.40	.76	1.40	.76	.83
	PLCD1000612	.37	.31	.81	.47	.70	.43	1.02	.51	.98	.46	.99	.48	.98
	PLC1200612	.38	.36	.84	.63	.74	.56	1.14	.75	1.14	.70	1.14	.72	.74
	PLCD1200612	.38	.33	.78	.49	.68	.44	.84	.49	.81	.43	.82	.44	.81
	PLC1600412	.38	.37	.87	.54	.95	.51	1.00	.70	.95	.64	1.00	.66	.95
	PLCD1600412	.37	.31	.61	.44	.57	.41	.78	.44	.78	.43	.75	.46	.78
	PLC1600612	.38	.37	1.00	.57	.95	.53	1.40	.80	1.40	.71	1.40	.73	1.40
	PLCD1600612	.38	.32	.71	.49	.63	.42	.89	.51	.96	.45	.92	.49	.97


NOTES:

PLC12 DIMENSIONS



Panel Dimensions

	PANEL OPENING	PANEL THICKNESS MAX.-MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	.30 - .02	13/16	11/16-24UNEF
COUPLING INSERTS	see drawing	.30 - .02	13/16	11/16-24UNEF



Coupling Bodies • POLYPROPYLENE



TERMINATION IN-LINE PIPE THREAD

PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†

PANEL MOUNT HOSE BARB

IN-LINE FERRULELESS POLYTUBE FITTING, PTF†

IN-LINE HOSE BARB

IN-LINE SOFTUBE™ FITTING

TUBING/THREAD SIZE METRIC EQ.

1/4" NPT
 1/4" BSPT
 3/8" NPT
 3/8" BSPT

3/8" OD, 1/4" ID 9.5mm OD, 6.4mm ID

1/4" ID 6.4mm ID
 3/8" ID 9.5mm ID

3/8" OD, 1/4" ID 9.5mm OD, 6.4mm ID

1/4" ID 6.4mm ID
 3/8" ID 9.5mm ID

3/8" OD, 1/4" ID 9.5mm OD, 6.4mm ID
 1/2" OD, 3/8" ID 12.7mm OD, 9.5mm ID

STRAIGHT THRU

PLC1000412
 PLC1000412BSPT
 PLC1000612
 PLC1000612BSPT

PLC1200612

PLC1600412
 PLC1600612

PLC1300612

PLC1700412
 PLC1700612

SHUTOFF

PLCD1000412
 PLCD1000412BSPT
 PLCD1000612
 PLCD1000612BSPT

PLCD1200612

PLCD1600412
 PLCD1600612

PLCD1300612

PLCD1700412
 PLCD1700612

PLCD17040612
 PLCD17060812

A

B

1.00 1.15
 1.00 1.15
 1.00 1.15
 1.00 1.15
 1.00 1.95

1.00 1.95
 1.00 1.95

1.02 1.96

1.02 1.96
 1.02 1.96

1.02 2.20
 1.02 2.36

PLC12 Coupling Readers • POLYPROPYLENE



TERMINATION IN-LINE HOSE BARB (RS-232 Interface)

IN-LINE HOSE BARB (USB Interface)

TUBING/THREAD SIZE METRIC EQ.

1/4" ID 6.4mm ID
 3/8" ID 9.5mm ID

1/4" ID 6.4mm ID
 3/8" ID 9.5mm ID

STRAIGHT THRU

SHUTOFF

iPLCDR1700400
 iPLCDR1700600

iPLCDR1700401
 iPLCDR1700601

A

B

1.39 2.78
 1.39 2.78

1.00 1.38/2.05
 1.05 1.74/1.87

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.
 †NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: JG is a registered trademark of John Guest USA, Inc.

Coupling Inserts • POLYPROPYLENE

	TERMINATION IN-LINE PIPE THREAD	TUBING/THREAD SIZE METRIC EQ.		STRAIGHT THRU PLC2400412	SHUTOFF PLCD2400412	A .72	B 1.26/1.67	D
		1/4" NPT						
	PANEL MOUNT HOSE BARB	1/4" ID	6.4mm ID	PLC4200412	PLCD4200412	.94	1.91/2.05	
		3/8" ID	9.5mm ID	PLC4200612	PLCD4200612	.94	1.91/2.05	
	IN-LINE FERRULELESS POLYTUBE FITTING, PTF†	3/8" OD, 1/4" ID	9.5mm OD, 6.4mm ID	PLC2000612	PLCD2000612	.72	1.68/1.82	
	IN-LINE HOSE BARB	1/4" ID	6.4mm ID	PLC2200412	PLCD2200412	.63	1.35/2.00	
		3/8" ID	9.5mm ID	PLC2200612	PLCD2200612	.63	1.35/1.82	
	IN-LINE SOFTUBE™ FITTING	3/8" OD, 1/4" ID	9.5mm OD, 6.4mm ID		PLCD22040612	.72	2.23	
		1/2" OD, 3/8" ID	12.7mm OD, 9.5mm ID		PLCD22060812	.72	2.18	
	ELBOW FERRULELESS POLYTUBE FITTING, PTF†	3/8" OD, 1/4" ID	9.5mm OD, 6.4mm ID	PLC2100612	PLCD2100612	.61/.62	1.29/1.36	.95
	ELBOW HOSE BARB	1/4" ID	6.4mm ID	PLC2300412	PLCD2300412	.63	1.22/1.36	.96
		3/8" ID	9.5mm ID	PLC2300612	PLCD2300612	.63	1.28/1.42	.96
	IN-LINE HOSE BARB (RS-232 Interface)	1/4" ID	6.4mm ID	iPLCT2200400	iPLCDT2200400	1.39	2.78	
		3/8" ID	9.5mm ID	iPLCT2200600	iPLCDT2200600	1.39	2.78	
	ELBOW HOSE BARB (RS-232 Interface)	1/4" ID	6.4mm ID	iPLCT2300400	iPLCDT2300400	1.48	1.27/1.40	
		3/8" ID	9.5mm ID	iPLCT2300600	iPLCDT2300600	1.48	1.33/1.46	

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted.

†NOTE: CPC's Ferruleless Polytube Fitting terminations do not require ferrules to achieve a secure connection, which makes them easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc. NOTE: JG is a registered trademark of John Guest USA, Inc.